



NOTES:  
 1).SPECIFICATIONS:  
 1.1.VOLTAGE RATING:100V AC  
 1.2.CURRENT RATING:1.0A  
 1.3.INSULATION RESISTANCE:100 MEG.OHM MIN.  
 1.4.CONTACT RESISTANCE:50 MILL.OHM MAX.  
 1.5.OPERATION TEMPERATURE:-30  
 1.6.INSERT FORCE:35 N MAX.  
 1.7.EXTRACT FORCE:8 N MIN.  
 1.8.DURABILITY:10000 CYCLES

° TO +80 °

3				
2				
1				
NO.	DESCRIPTION	MAT,L	COLOR	REMARK
<b>深圳市鑫南天科技有限公司</b> Shenzhen XinNanTian Industrial Co.,Ltd				
CUSTOMER COPY	TITLE: MICRO USB 5PIN 沉板0.93 四脚插板 无翻边			
PART NO.	XNTMICRO5PCB093PK			
PRODUCT SPEC.	XNTMICRO5P00200			
FILE NAME.	XNTMICRO5PCB093PK-C			
SCALE	UNIT:mm	A4	SHEET: of	

ECN(DCN) NO.	REV	DATE	DESCRIPTION	CHANGE	APPRO.	Angle ±2°	DESIGN	COCO
						X ±0.50	CHECK	JANY
						.X ±0.30	APPRO.	JEFF
						.XX ±0.15		
GENERAL TOLERANCE UNLESS OTHERWISE NOTED								